International Journal of Science Engineering and Advance Technology

A Novel Mechanism For Multipath Routing in MANET

[1]YakkaliVenkateshwara Gupta,[2]Nadella Sunil
[1]Final Master of Science in Computer Science, Ideal College of Arts and Science., Vidyut Nagar, Kakinada, East Godavari Dist., AP, India.
[2]Associate Professor, Department of Computer Science,Ideal college of Arts and sciences.,Vidyut Nagar, Kakinada ,East Godavari Dist, A.P, India.

ABSTRACT:

Energy consumption is careful as one of the mainlimits in MANET, as the mobile nodes do not ownperpetualcontrolstock and has to depend on batteries, thus dipping network era as batteries get exhausted very fast as nodes move and modification their positions rapidly across MANET. The study proposed in these weekly things to see this very specific problem of energy consumption in MANET by applying the Fitness Function technique to adjust the energy consumption in Ad Hoc on Demand Multipath Distance Vector (AOMDV) routing protocol. The proposed protocol is called Ad Hoc on Demand Multipath Distance Vector with the Fitness Function (FF-AOMDV). The capabilityjob is used to invention the optimal path from the mechanism to the destination to condense the energy consumption in multipath routing.

KEYWORDS: protocol, simulation time, packets.

1.INTRODUCTION:

Mobile ad hoc networks (MANETs) are intended to provisionreal and healthy mobile wireless network operation through the combination of routing functionality into mobile nodes. These networks are predicted to have topologies that are multihop, dynamic, random, and sometimes fast changing. These topologies will perhaps be collected of wireless links that are comparatively bandwidth-constrained. Ad hoc networks are critical in the development of wireless networks, as they are composed of mobile nodes which connect over wireless links deprived of central control. The traditional wireless and mobile communication problems like bandwidth optimization, transmission quality improvement and power control are straightcongenital by ad-hoc wireless networks. There have been many proposals on dissimilar approaches and protocols as there are manifoldcalibration efforts being done in the Internet Engineering Task Force and even as academic and industrial undertakings.

2.LITERATURE SURVEY:

2.1wedeliverenergy Entropy Multipath Routing optimization algorithm in MANET based on GA (EMRGA). The key idea of the protocol is to find the negligible node residual energy of each route in the course of choosing path by descendant node remaining energy. It can equilibrium individual nodes cordless power operation and laterlengthen the entire networks generation and live lines adjustment.

2.2 The approach efforts to interpretation for link firmness and is for lowest drain rate energy consumption. In order to validate the exactness of the proposed solution anunbiased optimization invention has been premeditated and a different routing protocol called Link-stability and Energy aware Routing protocols (LAER) is proposed. This novel routing scheme has been equaled with other three protocols: PERRA, GPSR, and E-GPSR. The protocol show has been evaluated in terms of Data Packet Delivery Ratio, Normalized Control Overhead, Link duration, Nodes lifetime, and Average energy consumption.

3.PROBLEM DEFINTION:

The importantimpression of the protocol was to discovery the negligible node remaining energy of each route in the course of selecting a path by descendent node residual energy. It can poisediscrete nodes battery power operation and laterlengthen the full networks time and livelinessmodification.

4.PROPOSED APPROACH:

In a typicalsetup, when a RREQ is disseminated by a source node, more than one route to the journey's end will be found and the data packets will be furthered through these routes short of knowing the routes' quality. By instigating the wished-for algorithm on the identical scenario, the direction selection will be whollyunalike. When a RREQ is broadcast and customary, the source node will have three types of

evidence in order to find the thru and heightened route path with decreasedenergy ingesting.

5.SYSTEM ARCHITECTURE:



6.PROPOSED METHODOLOGY:

SOURCE

Source browses the file, choice the destination and sends to the router. In Source while uploading the file, translate and then uploads the file. File contented will be adjusted to all the nodes.

ROUTER

Routercontains of four Networks, each Network covers specific nodes. When Basis sends the file originally it comes to the Network1 and permitsfinished the Network1 nodes, if any mobbing found in the Network1 node, Itmechanically selects another node an changes to Network2 and Network 3 and Network4 and spreads the destination. The energy size also beadapted, view the Network details. In router the routing path and time delay can be watched.

ROUTER MANAGER

Router manager views the attacker details by examination the energy details and find attackers.

DESTINATION

Receiver request for file name and secret key and receives the gratified from the router. Time delay will be intended by sending the file from source to destination and time taken to spread the destination.

ATTACKER

Attackerchoices the Network and node, gets the unique energy size and adapts the energy size for the node.

7.MULTIPATH ROUTING PROTOCOL

INPUT:v,V,R,r,e,E

Step1: Select the Source and Destination.
step2: Source Initialize the route Discovery.
Step3: Broadcast the Routing Packet to direct nodes.
Step4: Update the routing information in the Source Routing Table.
Step5: Source Initialize the Beacon.
Step6: Broadcast the Routing Packet to direct nodes.
Step7: Update the Energy and location information in the Source Energy Table for all the nodes in the entire network.
Step8: If(*ene*>= High &&*dist*<= Low &&*hop Count*<= Low)
Select that route for Communication.
Else if (*ene*>= High &&*dist*>= high &&*hop Count*<= Low)
Select that route for Communication.
Else if (*ene*<= Low&&*dist*<= Low &&*hop Count*<= Low t)
Select that route for Communication.
Step9: Send the periodic route discovery.
Step10: Send the periodic beacon message.

8.RESULTS



File TransferingAnd File Path Area To Select File And To Send File To Destination



Displays Nodes In Routers



Display Energy Levels Form Source To Destination



File received after sending file



NODE ENERGY DETAILS



ROUTING PATH DETAILS

EXTENSION WORK:

The anticipate dun principled routing scheme develops a buttressing culture background to deviously route the packets even in the lack of unswerving knowledge about frequency statistics and grid model. This organization is top with zero data regarding network topology and channel statistics. The future routing structure jointly discourses the questions of learning and routing in an unscrupulous background.

9.CONCLUSION:

A n innovativedynamismresourceful multipath routing algorithm called FF-AOMDV is virtualexpending NS-2 beneath three different scenarios, varying node speed, packet size and simulation time. These scenarios were verified by five performance metrics as Packet delivery ratio, Throughput, End-to-end-delay, Energy consumption and Network lifetime. Imitationconsequencepresented that the proposed FF-AOMDV algorithm has did much healthier than both AOMR-LM and AOMDV in amount, packet delivery ratio and end-to-end delay. It also did well in contradiction of AOMDV for preserving more vigor and healthiernetera.

10.REFERENCES:

[1] Macker, J. (1999). Mobile ad hoc networking (MANET): Routing protocol performance issues and evaluation considerations.

[2] Giordano, S. (2002). Mobile ad hoc networks.*Handbook of wireless networks and mobile computing*, 325-346.

[3] Perkins, C. E. (2001). Ad hoc networking: an introduction, Ad hoc networking.

[4] Zheng, S., Weiqiang, W. U., & Zhang, Q. (2011). Energy and link-state based routing protocol for MANET. *IEICE TRANSACTIONS on Information and Systems*, *94*(5), 1026-1034.

[5] Marina, M. K., & Das, S. R. (2006). Ad hoc on-demand multipath distance vector routing. *Wireless communications and mobile computing*, *6*(7), 9

[6] Tekaya, M., Tabbane, N., &Tabbane, S. (2010, November). Multipath routing mechanism with load balancing in ad hoc network. In *Computer Engineering and Systems (ICCES), 2010 International Conference on* (pp. 67-72). IEEE.

[7] Gatani, L., Re, G. L., &Gaglio, S. (2005, June). Notice of Violation of IEEE Publication Principles An adaptive routing protocol for ad hoc peer-to-peer networks. In Sixth IEEE international symposium on a world of wireless mobile and multimedia networks (pp. 44-50). IEEE.

[8] YogeshChaba, Patel, R. B., and Rajesh Gargi (2012). Issues and challenges involved in multipath routing with DYMO protocol. International Journal

of Information Technology and Knowledge Management, January-June 2012, 5(1), pp. 21-25.

[9] Mueller, S., Tsang, R. P., &Ghosal, D. (2004). Multipath routing in mobile ad hoc networks: Issues and challenges. In *Performance tools and applications to networked systems* (pp. 209-234).Springer Berlin Heidelberg.

[10] Balaji, V., &Duraisamy, V. (2011). Varying Overhead Ad Hoc on Demand Vector Routing in Highly Mobile Ad Hoc Network. Journal of Computer Science, 7(5), pp. 678-682.

[11] Poonam M. and Preeti D. (2014). Packet Forwarding using AOMDV Algorithm in WSN. International Journal of Application or Innovation in Engineering & Management (IJAIEM), 2319 – 4847, 3(5), May 2014, pp. 456-459.

[12] GimerCervera, Michel Barbeau, Joaquin Garcia-Alfaro, and EvangelosKranakis.(2013). A multipath routing strategy to prevent flooding disruption attacks in link state routing protocols for MANETs. Journal of Network and Computer Applications, 36(2), March 2013, 744-755.

[13] Marina, M. K., & Das, S. R. (2001, November). On-demand multipath distance vector routing in ad hoc networks.In*Network Protocols, 2001. Ninth International Conference on* (pp. 14-23). IEEE.

[14] Hu, Y. F., Ding, Y. S., Ren, L. H., Hao, K. R., & Han, H. (2015). An endocrine cooperative particle swarm optimization algorithm for routing recovery problem of wireless sensor networks with multiple mobile sinks. *Information Sciences*, *300*, 100-113.

[15] Montazeri, A., Poshtan, J., &Yousefi-Koma, A. (2008). The use of?particle swarm? to optimize the control system in a PZT laminated plate. *Smart Materials and Structures*, *17*(4), 045027.

[16]MueenUddin*[1],Aqeel Taha[1],Raed Alsaqour[2],Tanzila Saba[3].(2017).Energy efficient multipath routing protocol for mobile ad-hoc network using the fitness funcSSSStion

Mr. Yakkali Venkateswara Gupta is a student of IDEAL COLLEGE OF ARTS AND SCIENCE, KAKINADA. Presently he is in Final Master of Science inComputer Sciencethis college affiliated to Adikavi Nannaya University, Rajamahendravaram, AndhraPradesh. . His area of interest includes Computer Networks and Object oriented Programming languages.

Mr.NADELLA.SUNIL presently working as Director and Associate Professor in P.G Department of Computer Science Ideal college of Arts and Sciences, Kakinada. He obtained M..Sc (Applied Mathematics) from Andhra University, M.Phil in Applied Mathematics from Andhra university and did M.Tech (CSE) from UCE, JNTU kakinada. Received Professor. I. Venkata Rayudu Shastabdi Poorthi Glod Medal, Applied Mathematics. Prize from T.S.R.K Murthy Shastabdi Prize from Andhra university. Have LecturerShips in both Mathematical Sciences and ComputerScience and Applications Disciplines. Presently pursuing Ph.D in Computer Science from JNTU Kakinada.