Diagnosis And Detection Of Hepatitis Disease Using ML

Swetha Talabathula[1], Gangotri Kongarani[2], Kala Devi Nadimpalli[3], Bhairava Varma Pesingi[4], Jaswanthi Korasikha[5]Mrs. V. Sai Priya- Associate Professor[6]
[123456]Department of CSE, B. Tech, Srinivasa Institute Of Engineering And Technology, (Autonomous), NH-216, Cheyyeru(V), Krapa Chintalapudi(post), Katrenikona(M), Amalapuram, E.G.Dist-533216.

Abstract
The main goal of this research is to determine the optimum method for diagnosing and identifying hepatitis while also taking future patient expectations into consideration. This study involved the completion of a comparative report between several machine learning technologies and neural networks. The precision rate and mean square error both affect the exhibition metric. The Machine Learning (ML) techniques, such as Support Vector Machines (SVM), K Nearest Neighbor (KNN), and Artificial Neural Network (ANN), were thought of as the characterising and anticipating tools for diagnosing hepatitis infection. In light of the accuracy of the sickness diagnosis prediction, a brief report on the aforementioned algorithms was completed.

Key words- SVM, ANN, KNN, and Hepatitis 1 are key words.

INTRODUCTION:
Clinical examination is a necessary but extremely challenging process that calls for precise identification. It is crucial to diagnose the illness at the proper moment and to find relief as soon as possible. The liver is the basic component of the human body. Hepatitis, which aggravates the liver, is one of the severe diseases that affect the liver's usefulness. The presence of a liver infection is the main cause of hepatitis disease [1]. Hepatitis is a widespread disease with a high mortality rate. In the event that specific actions are not made in a timely manner, it may affect the vital body parts and increase the risk of developing cirrhosis, severe scarring, and liver cancer [2]. Early diagnosis using reliable conclusions and the right medication helps treat the illness. The two key elements for diagnosing any illness are (I) selecting the appropriate diagnostic parameters, and (ii) a thorough analysis of the data by knowledgeable experts.

Literature survey (n = 2) .1] A. H. Roslina, A. Noraziah, and other
Patients with hepatitis are those who require ongoing specific medical care to lower mortality rates. Clinical test results data and machine learning tools like Support Vector Machines (SVM) can be used to classify patients and predict their prognosis for survival. We cannot guarantee that every feature value in the data is associated to another, though. As a result, before classification, we employ Wrapper Methods to eliminate noisy features. This study demonstrates how combining feature selection and classification methods can improve data prediction.

Ghumbre (2.2) Including Shashikant Uttreshwar
This study looked into the use of artificial intelligence in the diagnosis of the common disease Hepatitis B. In this study, a generalised regression neural network and an intelligent system based on logical inference are given for the diagnosis. To determine if a patient may have Hepatitis B or another type of hepatitis, an expert system based on logical inference is used. The hepatitis B forecasts will then be made using artificial neural networks. The Generalized Regression Neural Network is used to analyse hepatitis data and make predictions about the severity of the patient's Hepatitis B infection.

3] CONCERN STATEMENT
For the analysis and expectation of illnesses, many investigations have been conducted [14]. In the projection of cutting-edge fibrosis that consolidates serum biomarkers, Somaya et al. evaluated various ML techniques [7]. Haydon et al. used fictitious

neural networks to simulate cirrhosis in individuals using standard clinical host and viral characteristics [4]. Jiaxin et al. established a programmed discovering framework to predict the fibrosis stage and incendiary action grade of chronic hepatitis C using outrageous learning machine on patient serum record information [8].

4] PROPOSED APPROACH:

In this study, the necessary data set is selected from the UCI repository while taking into account various clinical scenarios. This dataset has 155 instances and 20 attributes. One of the same attributes in this dataset determines how long a hepatitis patient will live. Table I lists the 19 attributes for classification. SVM and KNN machine learning algorithms were used to train and test on the dataset. The same dataset was then used for a performance study using a neural network approach. The effectiveness of the tool used for prediction as well as the mean square error were utilised to analyse the comparison. The performance is improved when the mean square error is lower.

5] SYSTEM ARCHITECTURE:

6] RECOMMENDED METHODOLOGY:

The data set, which consists of 155 instances with 20 attributes, was taken from the UCI repository. 75 of the 155 occurrences in this hepatitis database contain missing values. The data approach was utilised to obtain enough data for training, validation, and testing.

Data gathering: Gather sufficient samples of both legal software and data.
Data pre-processing: Process the sample's data well and extract its features.

Split the data into train and test data using the train and test modelling method. The model will be trained using Train, and performance will be evaluated using Test data.

Select more key features for the classification process.
SVM Navie Bayes, Random Forest, KNN, Ada Boost, Decision Tree, and Ada Boost with Random Forest are some modelling techniques. Create a classification model by combining the training data with machine learning methods.

8] RESULTS:

Data Count

Accuracy Comparison for all the models

9] CONCLUSION:

In this special case, brain networks and ML techniques were used to detect hepatitis. In order to identify the most effective method for determining whether someone has hepatitis, a study of the accuracy for a specific informative index was conducted using several ML and ANN techniques. To accurately predict the infection, we used Support Vector Machine (SVM), Artificial Neural Network (ANN), and K Nearest Neighbor (KNN). The conclusion drawn from this research is that, of all the models examined and their representations, ANN is the most precise, providing a respectable prediction precision of 96 percent and a base mean square error. In the future, similar work using RNN for the prediction of the occurrence of other diseases will be carried out.

10] REFERENCES:

[1] Ghumbre S. U.; Ghalot A.A, “Hepatitis B Diagnosis using Logical Inference And Self Organizing Map”, 2008 ; Journal of Computer Science ISSN 1549-3636.

[2] M. A. Chinnaratha, G. P. Jeffrey, G. Macquillan, E. Rossi, B. W. D. Boer, D. J. Speers, and L. A. Adams, “Prediction of morbidity and mortality in patients with chronic hepatitis c by non-invasive liver fibrosis models,” Liver International, vol. 34, no. 5, pp. 720–727, 2014.

[3] Roslina, A. H., and A. Noraziah. "Prediction of hepatitis prognosis using Support Vector Machines and Wrapper Method." In 2010 Seventh International Conference on Fuzzy Systems and Knowledge Discovery, vol. 5, pp. 2209-2211. IEEE, 2010.

[4] G. H. Haydon, R. Jalan, M. Alakorpela, Y. Hiltunen, J. Hanley, L. M. Jarvis, C. A. Ludlum, and P. C. Hayes, “Prediction of cirrhosis in patients with chronic hepatitis c infection by artificial neural network analysis of virus and clinical factors,” Journal of Viral Hepatitis, vol. 5, no. 4, pp. 255–264, 2010.

[5] Atif Khan, John A. Doucette, Robin Cohen, “Integrating Machine Learning into a Medical Decision Support System to Address the Problem of Missing Patient Data”, 2012 IEEE DOI 10.1109/ICMLA.2012.82.

[6] Uhmn, Saangyong, Dong-Hoi Kim, Young-Woong Ko, Sungwon Cho, Jaeyoun Cheong, and Jin Kim. "A study on application of single nucleotide polymorphism and machine learning techniques to diagnosis of chronic hepatitis." Expert Systems 26, no. 1 (2009): 60- 69.

[7] KayvanJoo, Amir Hossein, Mansour Ebrahimi, and Gholamreza Haqshenas. "Prediction of hepatitis C virus interferon/ribavirin therapy outcome based on viral nucleotide attributes using machine learning algorithms." BMC research notes 7, no. 1 (2014): 565.

[8] Vijayarani, S., and S. Dhayanand. "Liver disease prediction using SVM and Naïve Bayes algorithms." International Journal of Science, Engineering and Technology Research (IJSETR) 4, no. 4 (2015): 816-820.

[9] Sartakhti, Javad Salimi, Mohammad Hossein Zangooei, and Kourosh Mozafari. "Hepatitis disease diagnosis using a novel hybrid method based on support vector machine and simulated annealing

(SVMSA)." Computer methods and programs in biomedicine 108, no. 2 (2012): 570-579.

[10] Uttreshwar, Ghumbre Shashikant, and A. A. Ghatol. "Hepatitis B diagnosis using logical inference and generalized regression neural networks." In 2009 IEEE International Advance Computing Conference, pp. 1587-1595. IEEE, 2009.

[11] Ba-Alwi, Fadl Mutaher, and Houzifa M. Hintaya. "Comparative study for analysis the prognostic in hepatitis data: data mining approach." spinal cord 11 (2013): 12.

[12] Yildirim, Pinar. "Filter based feature selection methods for prediction of risks in hepatitis disease." International Journal of Machine Learning and Computing 5, no. 4 (2015): 258.

[13] Chen, Hui-Ling, Da-You Liu, Bo Yang, Jie Liu, and Gang Wang. "A new hybrid method based on local fisher discriminant analysis and support vector machines for hepatitis disease diagnosis." Expert Systems with Applications 38, no. 9 (2011): 11796-11803.

[14] Lalithamani N., Amrutha C., "Efficient storage and retrieval of medical records using fusion-based multimodal biometrics", International Journal of Computer Aided Engineering and Technology, Volume 10, Issue 5, 2018, Pages 576-588.