International Journal of Science Engineering and Advance Technology

Speech Emotion Verification Using Emotion Variance And Discriminate Scale Frequency Maps

[1*]P.Sunitha ,[2]E. Lakshmi Shravya
[1]Department-ECE, Pragati Engineering College, Surampalem (AP), India.
[2]Department-ECE, Pragati Engineering College, Surampalem (AP) India.
eadharashravya3@gmail.com

ABSTRACT
The problems of emotion variances and emotion blending are solved using the emotion verification system. In this methodology consists of two parts. The first part, feature extraction is used to lessen the huge input data into smaller data. The second part, emotion verification can automatically verify and authenticate users from their voice or speech. For each sound frames, vital atoms from the Gabor dictionary are selected by the using of vector quantization. Each atom within the dictionary takes the form of a Gabor function which includes frequency, scale etc.Sparse representation is used to convert scale-frequency maps into sparse coefficients to enhance the robustness towards emotion variance.After the feature extraction, a fusion mechanism is applied the subsequent two strategies. The first is the sparse representation verification based on Gaussian modeled residual errors which can be accommodate emotion variance within the voices of speakers. Such a classifier can be reduce emotion variance and improve recognition accuracy. The second, is to involves the use of an indicator, the EAI, for the measuring the degree of blended emotions. The two scores have been calculated they are fused with each other. It also verifies the performance as well as feasibility.

KEYWORDS: Emotion Speech Recognition, Gaussian –Modeled Residual Error, Sparse Representation, Scale- Frequency Maps

1. INTRODUCTION:

Emotion recognition systems are based on facial or voice features. This paper shows the execution of a voice-based emotion detection system reasonable to be utilized over smart phone stages and ready to perceive six emotion (anger, fatigue, appall, fear, joy, trouble) and the impartial state, as broadly utilized for emotion recognition. The principle commitments of this paper concern: i) a framework ready to perceive individuals feelings made out of two subsystems, Gender Recognition (GR) and Emotion Recognition (ER); ii) a gender recognition algorithm, in view of pitch extraction, and went for giving from the earlier data about the gender of the speaker; iii) a SVM-based emotion classifier, which utilizes the gender data as input. Lessened capabilities, acquired by highlight choice, Performed through Principal Component Analysis (PCA), have been researched and connected. With a specific end goal to prepare and test the said SVM based emotion classifier, a broadly utilized passionate database (called Berlin Emotional Speech Database, BESD) has been utilized. The two forms of emotion variance are considered in this paper, first is the inter – emotion varianceis defined as inconsistent emotional presentation among multiple people owing in their characteristics. Intra-emotion variance is defined as emotion is expressed in different ways at various times by a single speaker. To solve the problem that caused by blended emotions and emotion variances by using speech emotion verification system.

2. BLOCK DIAGRAM:

This block diagram is divided into two parts. The first part is the feature extraction is a required entity. The second part, emotion verification can automatically verify and authenticate users from their voice or speech. In the first part, for each sound frames, vital atoms from the Gabor dictionary are selected by the using of vector quantization. This algorithm is based on the coefficients. Calculating the difference in the coefficients is referred as discriminating. Emotion

variance often leads to recognition biases even when a slight difference is present in same emotion kind to deal with such problem, then it identify by Gaussian residual error. Further work applied Gaussian –modeled residual error to verification tasks which is known as sparse representation verificationEAI (Emotional Agreement Index) is to compare and classify the values and then check it.

3. METHODOLOGY:

Centre of gravity (COG)

The spectral Centre Of Gravity (COG) is a measure of the way high the frequencies in a spectrum. For this reason the COG gives an average Indication of the spectral distribution of the speech signal under observation. Centre of gravity is the point in a frame round which the resultant torque because of gravity forces vanishes.Given the considered discrete sign s(n) and its DFT S(k), the COG has been computed by using:

$$f_{COG} = \frac{\sum_{k=1}^{N} f_k \, |S(k)|^2}{\sum_{k=1}^{N} |S(k)|^2}$$

Spectrum Central Moments*:*

The m-th central spectral moment of the taken into consideration sequences(n) has been computed by means of:

$$\mu_m = \frac{\sum_{k=1}^{N} (f_k - f_{COG})^m \, |S(k)|^2}{\sum_{k=1}^{N} |S(k)|^2}$$

In probability theory and statistics, a central moment is a moment of a probability distribution of a random variable approximately the random variable's mean. The rth moment approximately any point a is known as a central moment

Skewness:

The skewness of a spectrum is a measure of symmetry and it is defined as the third central moment of the taken into consideration series s (n), divided through the 1.5 power of the second central moment:

$$\gamma_1 = \frac{\mu_3}{\sqrt{\mu_2^3}}$$

Kurtosis:

The excess of Kurtosis is defined because the ratio among the fourth central moment and the square of the second central moment of the taken into consideration series s (n) minus 3:

$$\gamma_2 = \frac{\mu_4}{\mu_2^2} - 3$$

Standard deviation:

In statistics, the standard deviation is a degree this is used to quantify the quantity of version or dispersion of a fixed of data values. The standard deviation of a continuous real-valued random variable X with probability density function $p(x)$ is

$$\sigma = \sqrt{\int_{\mathbf{X}} (x-\mu)^2 p(x)\,dx}, \quad \text{where } \mu = \int_{\mathbf{X}} x p(x)\,dx.$$

Standard deviation is quite a number used to tell how measurements for a group are spread out from the average (mean), or expected value. A low standard deviation approach that most of the numbers are very near the average. A high standard deviation way that the numbers are spread out.

4. EXPERMENTAL RESULTS:

Simulation waveform for Happiness recognition

CONCLUSION:

The overall performance analysis suggests the accuracy received with the followed emotion recognition system in phrases of recognition rate and the percentage of efficiently recognized emotional contents. . The results display that with the employment of a features selection algorithm, a satisfying recognition rate level can nonetheless be acquired also reducing the employed functions.

REFERENCE

[1] W. H. Abdulla and N. Kasabov, “Improving speech recognition performance through gender separation,” in Proceedings of the International Conference on Artificial Neural Networks and Expert Systems (ANNES), Dunedin, New Zealand, 2001, pp. 218–222.

[2] D. W. Aha, D. Kibler, and M. K. Albert, “Instance-based learning algorithms,” Machine Learning, vol. 6, no. 1, pp. 37–66, January 1991.

[3] H. Ai, D. J. Litman, K. Forbes-Riley, M. Rotaru, J. Tetreault, and A. Purandare, “Using system and user performance features to improve emotion detection in spoken tutoring dialogs,” in Proceedings of the 9th International Conference on Spoken Language Processing (INTERSPEECH), Pittsburgh, PA, USA, September 2006.

[4] K. Alter, E. Rank, S. A. Kotz, U. Toepel, M. Besson, A. Schirmer, and A. D. Friderici, “Affective encoding in the speech signal and in event-related brain potentials,” Speech Communication, vol. 40, no. 1–2, pp. 61–70, April 2003.

[5] A. Álvarez, I. Cearreta, J. M. López, A. Arruti, E. Lazkano, B. Sierra, and N. Garay, “Feature subset selection based on evolutionary algorithms for automatic emotion recognition in spoken Spanish and standard Basque language,” in Proceedings of the 9th International Conference on Text, Speech and Dialogue (TSD), Brno, Czech Republic, September 2006, pp. 565–572.